

RAIL MOUNT HINGE INSTALLATION

Thank you for choosing Paddle King! Your add-on Rail Mount Hinge kit includes:

(2) Rail Hinges with Safety Pins (4) 1/4-20 x 1 3/4" SS Truss Bolts (4) 1/4-20 SS Hex Flange Nut

1. Locate the rear hinge that is already on the rail.
2. Measure 54 3/4" from the stern edge towards the bow. This becomes the center of the new hinge that you are installing.
3. Center the new rail mount hinge at the measurement. Mark the two mounting holes.
4. Using a 1/4" drill bit, drill a hole completely thru the square railing at each of the mounting hole locations.
5. Place the hinge back on the rail with the holes aligned.
6. Insert the bolt thru the hinge and the rail.
7. Secure with the nut.

Your new rail mount hinges are now ready to use!



HOW TO USE RAIL MOUNT HINGES

FOR SAFETY PURPOSES: This process requires TWO people.

After your new add-on Rail Mount Hinges have been installed, remove the bolt and nut on the middle hinge that is holding the front canopy leg. Move the front canopy leg to the front hinge and insert the safety pin. This will lay the canopy down for trailering or storing. When you are ready to use your canopy, remove the safety pin, place the canopy leg back into the middle hinge and insert the safety pin once again.